



Tipo WH



CK60 / 1.1221

Referencia Type	Diámetro Diameter	Diámetro interior Inside diameter	Peso Weight	Longitud Estándar Length	Profundidad Temple Surface hardness depth DIN6773 Rht	Tolerancia Estandar Tolerance	Rodondez Roundness	Paralelismo Parallelism	Rectitud Straightness
	Ø D	d (+/-10%)	Kg/M	mm	mm	ISO h6	t1	t2	t3
	mm	mm				µm	µm	µm	mm/m
WH16	16	7	1,28	6 000	1,1 - 1,5	0/-11	8	11	0,30
WH20	20	14	1,25	6 000	1,2 - 1,5	0/-13	9	13	0,20
WH25	25	15,6	2,35	6 000	1,5 - 1,7	0/-13	9	13	0,20
WH30	30	18,3	3,50	6 000	1,5 - 1,9	0/-13	9	13	0,20
WH40	40	28	4,99	6 000	1,9 - 2,0	0/-16	11	16	0,10
WH50	50	29,7	9,91	6 000	2,2 - 2,6	0/-19	11	16	0,10
WH60	60	36	14,20	6 000	2,2 - 2,6	0/-19	13	13	0,10
WH80*	80	57	19,43	6 000	2,2 - 2,6	0/-19	13	13	0,10

Dureza superficial Surface hardness 60+/-3HRC  
 Ø Disponible en stock Ø available on stock  
 \* Consultar \*On request

